


SPEED GEARBOXES



HSG SERIES

TECHNICAL DATA

	Torque capacity	Max. speed	Speeds	Clutch housing	Clutch diameter	Output for	Output rotation								
	Nm	rpm						No.	mm	1 st	2 nd	3 rd	4 th	1 st	2 nd
HSG 50	50	3.300	4	B	187	2WD	Forward	5,32	3,25	1,81	1,00	5,32	3,25	1,81	1,00
HSG 50/32	50	3.300	4	B	187	2WD	Reverse	8,16	4,98	2,78	1,53	8,16	4,98	2,78	1,53
HSG 50/33	50	3.300	4	B	187	2WD	Reverse	19,87	12,12	6,77	3,73	19,87	12,12	6,77	3,73
HSG 50/26	50	3.300	4	B	187	4WD	Forward	23,78	14,50	8,10	4,47	23,78	14,50	8,10	4,47
HSG 50/30	50	3.300	4	B	187	4WD	Reverse	18,30	11,16	6,23	3,44	18,30	11,16	6,23	3,44
HSG 50/30L	50	3.300	4	B	187	4WD	Forward	24,70	15,06	8,41	4,64	24,70	15,06	8,41	4,64
HSG 50/30LI	50	3.300	4	B	187	4WD	Forward	24,70	15,06	8,41	4,64	24,70	15,06	8,41	4,64
HSG 70	70	3.500	4	B	187	2WD	Forward	5,32	3,25	1,81	1,00	5,32	3,25	1,81	1,00
HSG 70/32	70	3.500	4	B	187	2WD	Reverse	8,16	4,98	2,78	1,53	8,16	4,98	2,78	1,53
HSG 70/33	70	3.500	4	B	187	2WD	Reverse	19,87	12,12	6,77	3,73	19,87	12,12	6,77	3,73
HSG 70/26	70	3.500	4	B	187	4WD	Forward	23,78	14,50	8,10	4,47	23,78	14,50	8,10	4,47
HSG 70/30	70	3.500	4	B	187	4WD	Reverse	18,30	11,16	6,23	3,44	18,30	11,16	6,23	3,44
HSG 70/30L	70	3.500	4	B	187	4WD	Forward	24,70	15,06	8,41	4,64	24,70	15,06	8,41	4,64
HSG 70/30LI	70	3.500	4	B	187	4WD	Forward	24,70	15,06	8,41	4,64	24,70	15,06	8,41	4,64
HSG 100	100	3.300	4	9LD	215	2WD	Forward	5,70	3,11	1,69	1,00	5,70	3,11	1,69	1,00
HSG 100/32	100	3.300	4	9LD	215	2WD	Reverse	8,74	4,78	2,59	1,53	8,74	4,78	2,59	1,53
HSG 100/33	100	3.300	4	9LD	215	2WD	Reverse	21,28	11,63	6,31	3,73	21,28	11,63	6,31	3,73
HSG 100/35	100	3.300	4	9LD	215	4WD	Reverse	19,60	10,70	5,81	3,44	19,60	10,70	5,81	3,44
HSG 100/35L	100	3.300	4	9LD	215	4WD	Forward	26,45	14,45	7,85	4,64	26,45	14,45	7,85	4,64
HSG 120	120	3.300	4	5LD	250	2WD	Reverse	5,63	3,07	1,67	0,99	5,63	3,07	1,67	0,99
HSG 120/33	120	3.300	4	5LD	250	2WD	Reverse	13,70	7,49	4,07	2,40	13,70	7,49	4,07	2,40
HSG 120/31L	120	3.300	4	5LD	250	4WD	Forward	9,42	5,14	2,79	1,65	9,42	5,14	2,79	1,65
HSG 200	200	3.300	4	5LD	250	2WD	Forward	6,55	3,35	1,73	1,00	6,41	3,28	1,69	0,98

Features and benefits:

- 4 speed
- Reversing gear
- Aluminium/Silicium alloy case
- HQ bearings
- Reducer for 2/4 wheels drive
- Wide assortment of standard & special coupling flanges
- Slutch equipped
- Special ratios available