

DISTRIBUTORS



HD SERIES

TECHNICAL DATA

		Elements/ Sections	Nominal flow L/min	Max. operating pressure bar	Max. back pressure	Valves	Circuit	Action	Standard threads		
									P	A/B	T
									" BSP		
Monoblock	HDM 35	1	35	250	30	R	P	D	3/8	3/8	3/8
	HDM 45	1 ÷ 6	45	350	40	R	P, S	S, D	3/8 1/2	1/2	3/8 1/2
	HDM 70	1 ÷ 6	70	350	30	R	P, S	S, D	3/4 1/2	1/2	3/4 1/2
Sectional	HDS 67	1 ÷ 10	67	315	30	R, C	P, S	S, D	1/2	1/2	1/2
	HDS 80	1 ÷ 9	80	350	30	R, C	P, S	S, D	1/2 3/4	1/2 3/4	1/2 3/4
	HDS 150	1 ÷ 9	150	315	30	R, C	P, S	S, D	3/4	3/4	3/4 1

Valves	R	adjustable direct operated relief valve
	C	load hold check valve in each section
Circuit	P	parallel
	S	series
Action	S	single
	D	double

Recommended oil viscosity (100°C): 5,4 ÷ 11,4 cSt

Recommended max. oil filtering: 30 µm